




YUR.PHOTO 9B2 9" Digital Photo Frame



create >> excite >> inspire

The Spectrum of Revolution





YUR.PHOTO 9B29" Digital Photo Frame

Specifications

Display screen

Resolution

Aspect Ratio

Lumination Brightness

Contrast

Display position

Viewing Angle

Card Reader

Built-in Memory

USB interface

Response Time

Photo image support

OSD menu

Operating Temperature

Storage Temperature

Color

Controls

User Manual (Languages)

Power

· Certification/Regulation

Product Dimension
 Giftbox Dimension

Weight

Others

Accessories

AC / DC Power Adapter

Warranty Notice: *2 years Warranty

User Manual

Removable Stand

9" (22.86cm) display screen

640 x 220

16:9/4:3/Full Screen display Ratio Selection

250cd/m²

350:1

Image rotates 90° automatically when the frame is turned

120° (H) / 110° (V)

Support SD / MMC / MS / XD cards (4GB)

No

USB 2.0 HighSpeed, Compatible with mass-storage devices

30ms

JPEG, Zoom function, Automatic Looping

Multilingual: English, German, French, Italian, Spanish, Dutch

10° ~ 40° Celsius -20° ~ 80° Celsius

White Frame

Slide out control panel design, HotKey design for easy

access to each function. Power On/Off function.

Multilingual as per OSD (6 languages)

DC12V (Operating) / Max 8W (Consumption)

Dual DC-IN Jacks for desktop and wallmount usage

CE

270(W) x 186(H) x 43.2(D) mm 275(W) x 210(H) x 105(D) mm

690g (Unit) / - kg (Product package)

"Lock Slot" for cable-lock usage in public areas

Auto Rotation of Pictures with frame position placed

System Requirements

• SD / MMC / MS / XD cards up to 4GB capacity

USB Memory Stick with JPEG pictures

100 ~ 240V power supply

EAN: 8886437000835

Ver.: 2.0





create >> excite >> inspire

Yuraku Pte Ltd

40 Ubi Crescent, #01-02 Ubi Techpark, Singapore 408 567 Tel: +65 6238 2158

Fax: +65 6238 2158

Fax: +65 6238 0076

Website: www.yuraku.com.sq

Product image, Terms and Specifications are subjected to change without notice. ©2008 YURAKU PTE LTD