





Specifications


• Panel Type	288 Wp Monocrystalline silicon photovoltaic module
• Maximum Power (Pmax)	288 W
• Voltage @ Pmax (Vpm)	36,5 V
• Current @ Pmax (Ipm)	7,89 A
• Open Circuit Voltage (Voc)	45,0 V
• Short Circuit Current (Isc)	8,57 A
• Output Tolerance	± 3 %
• Maximum System Voltage	1000 Vdc
• Series fuse rating	10 A
• Application	DC 36V system
• Efficiency of module	14,86 %
• Temperature Coefficients of Pmax (%)	-0,5 % /°C
• Temperature Coefficients of Voc (%)	-0,33 % /°C
• Temperature Coefficients of Isc (%)	+0,035 % /°C
• Operating Temperature	-40 to +85 °C
• Storage Temperature	-40 to +85 °C
• System Cell	6" Monocrystalline silicon
• No. of cells & connections	72 pcs in series (6x12)
• Module Size (WxLxH)	1948 x 995 x 50 mm
• Weight	Approximately 22,95 Kg
• Packing configuration	Horizontal
• Size of carton	2005 x 1071 x 955 mm
• Pallet quantity	18 pcs / pallet
• Container Load (20ft/40ft)	10 pallets / 22 pallets

I-V Curves



Construction

• Front	High transmission low-iron tempered glass (3.2 mm)	Module dimension
• Back	PET / PET / EVA	
• Encapsulates	EVA	
• Junction Box Type	IP65, waterproof	
• Bypass Diodes	3 diodes to avoid power decreasing by shade	
• Output cable	4 mm ² cable with polarized waterproof tyco connectors (Negative 900 mm, Positive 900 mm)	
• Frame (Material, Corners, etc)	Clear anodized aluminium, AL6063-T5	
• Certification	IEC 61215 : 2005 + EN 61730-1 / EN 61730-2 : 2007	



measured at STC (Standard Test Condition; 1000 W/m² irradiance, AM 1.5G and 25 °C)

Warranty Notice: 5 years on materials. 10 years of 90 % output, 25 years of 80% output.

EAN : TBA

Yuraku Pte Ltd
 11 Collyer Quay,
 #10-04 The Arcade, Singapore 049 317
 Tel: +65 6238 2158
 Fax: +65 6238 0076
 Website: www.yuraku.com.sg

Yuraku S.r.l
 Via Fratelli Rosselli 3/2
 20019 Settimo Milanese (Milano) Italy
 Tel: +39 02 3351 4444
 Fax: +39 02 3359 0580
 Website: www.yuraku.it

Yuraku, SL
 C/Florida N° 1 (nave 4) Pol. Ind. Villapark
 28670 Villaviciosa de Odón (Madrid) España
 Tel: +34 91 6657 423
 Fax: +34 91 6166 324
 Website: www.yuraku.es

create >> excite >> inspire

Terms and Specifications are subjected to change without notice.
 ©2011 YURAKU PTE LTD